



# HTC Warhawk Screen Replacement

Disassembling the HTC Warhawk and replacing the screen.

Written By: Meuwissenm






## TOOLS:

- [Spudger](#) (1)
  - [T5 Torx Screwdriver](#) (1)
-

## Step 1 — Screen



- Take the back cover off the phone and take the battery out.

## Step 2



- Take a SL#2.5 screwdriver and pop the black piece off shown here.




### Step 3



- Take a T5 screwdriver and unscrew the two screws seen here


### Step 4



- Unscrew the two screws on the back of the phone with a T5 screwdriver




## Step 5



- Take the SL#2.5 screwdriver and pry off the back cover
- The phone should now look like the second picture


## Step 6



- Next lift up the camera lens from the board.
- Then pry off the circuit circled in red on the second picture




## Step 7



- Take the SL#2.5 screwdriver and pry off the volume buttons on the side of the phone
- The circuit board should now be detached from the LCD part of the phone

## Step 8



- Next take the SL#2.5 screwdriver and pry the grey fabric sticker off on the LCD side of the phone

## Step 9



- Next take the SL#2.5 screwdriver and pry the screen from the front plastic cover
- The screen should come out with ease and be completely detached from the rest of the cover.

## Step 10



- Replace screen with a new one.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-23 05:07:48 PM.